

Safety / Spectacles / 506 UP

506 UP - Clear Plus 1

Code: 506U.03.00.00

Date: 03-08-22 1/2

506 UP presents technical and aesthetic improvements. The panoramic and wrapping lens is available with Vanguard Plus coating for superior performance in all conditions. The temples with rubber tips and adjustable in length and inclination, the total adaptability of the nosepad and the new range of vibrant colors allow a high degree of customisation of the device.



Frame mark (EU)

506U U 166 FT CE

Lens mark (EU)

2C-1.2 U 1 FT K N CE

Conditions of use

Standard brightness, Low brightness

Lens color

Clear

Frame technology

Nose pad set-up, Adjustment of temples in length, Adjustment of temples in inclination

Lens technology

Anti-Scratch + Anti-Fog (KN - Vanguard PLUS)

Lens material

Polycarbonate

Frame color

White/Green

Standards

EN166, EN170

Scale number

(2C-1.2)

Mechanical resistance

Low energy impact (F)

Optical class

Optical class (1)

Optional requirements

Resistance to surface damage by fine particles (K), Resistance to fogging of oculars (N), Protection against high speed particles at extreme temperatures -5°/+55° C (T)

Weight

25g

>> <https://www.univetsafety.com/en/products/safety/spectacles/506-up/506-up-clear-plus-1/>



01.

TEMPLES ADJUSTABLE IN LENGTH
AND INCLINATION

02.

OPTIMAL COMFORT AND FIT
THANKS TO THE SOFT ADJUSTABLE
NOSE PAD

03.

PANORAMIC AND WRAPAROUND
LENS FOR A BETTER SIDE
PROTECTION

04.

SOFT TERMINAL TIPS TO ELIMINATE
LOCAL PRESSURE

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.

HEADQUARTERS

Univet S.r.l. Via Giovanni Prati 87 25086 Rezzato - Telephone 030 2499411 - Fax 030 2499430 - info@univetsafety.com
VAT. IT02506570163