

# DANCE S1P

KU055HF

CE UNI EN ISO 20345:2012 S1P SRC ESD

Low safety shoe, suede back leather thickness 1,8 - 2,0 mm

External 3D fabric, perspiring and abrasion resistant.

Soft, lined and padded tongue.

**COMPLETELY METAL FREE SHOE**

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE KUBE** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 5000, three-materials extracomfort:** perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoe satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance

**ESD**

**Size 35-42 Shoe weight Sz 42 gr. 485**



## CERTIFICATIONS



**AIRNET®**

## SECTORS



## SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product. This sole is called Kube, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole. With thanks to these special characteristics Kube obtained the maximum certification against slipping: jobs on inclined roofs (UNI 11583:2015).

## PLUS



**AIRNET®**

Airnet® is a certified technology that guarantees the maximum perspiration of the foot by wearing a strong and abrasion resistant safety shoe. Thanks to its construction air tunnel, facilitates the air passage and the material, 100% polyester, guarantees a perfect resistance to abrasion, to traction, to tearing and to washing.

## ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS		
	request	results
SRA ceramic + NaLS	HEEL $\geq$ 0,28	0,37
	FLAT $\geq$ 0,32	0,39
SRB steel + glycerol	HEEL $\geq$ 0,13	0,20
	FLAT $\geq$ 0,18	0,30

