



TEGERA® 866

Synthetic glove, PU, palm-dipped, polyester, 13 gg, smooth finish, Cat. II, black, breathable back, oil and grease resistant palm, for precision work

PROPERTIES

Flexible, durable, breathable, light

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE 6, 7, 8, 9, 10, 11

LINER MATERIAL Polyester, 13 gg

DIPPING Palm-dipped

DIPPING MATERIAL PU

DEXTERITY 5

GRIP PATTERN Smooth finish

CUFF STYLE Knitwrist cuff

LENGTH RANGE 220 - 260mm

COLOUR Black

PAIRS PER PACKAGE/CARTON 6/120

DISPLAY Bag

MATERIAL SPECIFICATION Polyurethane 70%, polyester 30%

SIZE	ART. NO.	EAN NO.
6	866-6	7392626070981
7	866-7	7392626063471
8	866-8	7392626063488
9	866-9	7392626063495
10	866-10	7392626063501
11	866-11	7392626063518

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 866

FEATURES

Oil and grease resistant palm

PRIMARY PROTECTION

Prevents risk of, abrasion injuries, scratches, lacerations, contact with dirt, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Oil and greasy environments, dirty environments

PRIMARY AREAS OF USE

Fine assembly, assembly, inspection work, building and construction, carpentry, installation work, HVAC installation, construction, soil preparation, engineering, machine driving, warehouse work, gardening, repair work

PRIMARY INDUSTRIES OF USE


Machinery and equipment, MRO, automotive, transportation, utilities

TYPE OF WORK

Light weight



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2016-06-27

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 866

EC TYPE EXAMINATION

Notified Body: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07 France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks


Property	Level Achieved	(Maximum Performance)
A) Resistance to wear (No. of revolutions)	4	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection	1	2	3	4	5
A) Resistance to wear (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2016-06-27

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com