## **TEGERA®**



MicroThan®4





## **TEGERA® 9122**

Synthetic leather glove, winter-lined, 0,7 mm Microthan®+, diamond grip pattern, polyester, fleece, Cat. II, black, grey, yellow, chrome free, water repellent, Velcro®, for allround work

#### **PROPERTIES**

Flexible, very durable, excellent grip, perfect fit, extra comfortable

#### **SPECIFICATION**

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11

PALM MATERIAL Microthan®+

PALM THICKNESS 0,7 mm

BACK MATERIAL Polyester

LINING Winter-lined

LINING MATERIAL Fleece

DEXTERITY 5

**GRIP PATTERN Diamond grip pattern** 

FASTENING Velcro®

LENGTH RANGE 242-282 mm

COLOUR Black, grey, yellow

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Hook with hangtag

 $\hbox{OUTER MATERIAL SPECIFICATION } \textbf{Polyurethane, nylon,} \\ \textbf{polyester} \\$ 

MIDDLE MATERIAL SPECIFICATION Polyethylene

INNER MATERIAL SPECIFICATION Acrylic

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2018-03-05 www.ejendals.com

## **TEGERA®**



 $\epsilon$ Cat. II







#### All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

### **TEGERA® 9122**

#### **FEATURES**

Chrome free, reinforced index finger, reinforced seams, reinforced fingertips, pre-curved fingers, specially designed thumb, water repellent, ergonomically shaped, reflector, specially designed details

#### **PRIMARY PROTECTION**

Prevents risk of:, chrome allergy, abraision injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with damp, contact with cold

#### PRIMARY ENVIRONMENTS OF USE

Dark environments, slippery environments, dry environments, cold environments, moist environments, oily and greasy environments, dirty environments

#### **PRIMARY AREAS OF USE**

Building and construction, carpentry, HVAC installation, construction, soil preparation, engineering, transport work, machine driving, warehouse work, airport work, metalwork, mining, forest work, agricultural work, gardening, paper industry work

#### PRIMARY INDUSTRIES OF USE

Agriculture, mining, oil, gas, petrochemical, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, transportation, utilities, building and construction, logistics, HoReCa, facilities, service, retail

#### **TYPE OF WORK**

Medium weight



**EJENDALS AB** 

Box 7, SE-793 21 Leksand, Sweden Phone +46 (0) 247 360 00 Fax +46 (0) 247 360 10

> info@ejendals.com order@ejendals.com

## **TEGERA®**



# CE Cat. II

EN 388:2003





# All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## **TEGERA® 9122**

#### **ECTYPE EXAMINATION**

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

#### **COMPLIANCE DESCRIPTION**

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level (Maximum Achieved Performance		
A) Resistance to abrasion (No. of revolutions)	1	(4)	
B) Resistance to cutting (Index)	2	(5)	
C) Tear resistance (Newton)	2	(4)	
D) Puncturing resistance (Newton)	1	(4)	

# EN 388 – Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 511:2006 Protective gloves against cold



**EJENDALS AB** 

Box 7, SE-793 21 Leksand, Sweden Phone +46 (0) 247 360 00 Fax +46 (0) 247 360 10

> info@ejendals.com order@ejendals.com